








Version	back section	required segment in front	parallelogram rod		max lift height	max lift height column adapter		max capacity	length of crane arm	
			front	back		without	with		ahead*	rear**
 Platform P_1	1,0 m	1 x 1,5 m	1 x 1,5 m	1 x 1,0 m	3,71 m	3,46 m	3,79 m	250 kg	2,77 m	1,97 m
	1,5 m	1 x 1,5 m	1 x 1,5 m	1 x 1,5 m	3,71 m	3,02 m	3,69 m	250 kg	2,77 m	2,45 m
 Platform P_2	1,0 m	3 x 1,5 m	9 x 1,5 m	3 x 1,0 m	8,63 m	5,92 m	6,25 m	135 kg	5,80 m	1,97 m
	1,5 m	3 x 1,5 m	9 x 1,5 m	3 x 1,5 m	8,63 m	4,89 m	5,95 m	180 kg	5,80 m	2,45 m
 Remote R_1	1,0 m	1 x 1,5 m	1 x 1,5 m	1 x 1,0 m	3,71 m	3,82 m	4,15 m	80 kg	3,01 m	1,97 m
	1,5 m	1 x 1,5 m	1 x 1,5 m	1 x 1,5 m	3,71 m	3,38 m	4,05 m	80 kg	3,01 m	2,45 m
 Remote R_2	1,0 m	3 x 1,5 m	9 x 1,5 m	3 x 1,0 m	8,63 m	6,28 m	6,61 m	80 kg	6,05 m	1,97 m
	1,5 m	3 x 1,5 m	9 x 1,5 m	3 x 1,5 m	8,63 m	5,25 m	6,42 m	80 kg	6,05 m	2,45 m
 Remote R_3	1,0 m	4 x 1,5 m	10 x 1,5 m	3 x 1,0 m	11,08 m	7,05 m	7,83 m	80 kg	7,57 m	1,97 m
	1,5 m	4 x 1,5 m	10 x 1,5 m	3 x 1,5 m	11,08 m	6,18 m	7,54 m	80 kg	7,57 m	2,45 m
 Remote R_4	1,0 m	5 x 1,5 m	13 x 1,5 m	3 x 1,0 m	13,54 m	8,49 m	8,82 m	65 kg	9,90 m	1,97 m
	1,5 m	4 x 1,5 m + 1 x 1 m	12 x 1,5 m + 1 x 1 m	3 x 1,5 m	13,54 m	7,12 m	8,70 m	65 kg	9,90 m	2,45 m
 Remote R_5	1,0 m	5 x 1,5 m + 2 x 1 m	15 x 1,5 m + 4 x 1 m	3 x 1,0 m	16,84 m	10,38 m	10,72 m	45 kg	11,13 m	1,97 m
	1,5 m	4 x 1,5 m + 3 x 1 m	12 x 1,5 m + 7 x 1 m	3 x 1,5 m	16,84 m	8,38 m	10,27 m	65 kg	11,13 m	2,45 m

Max counterweight = 768 kg \* camera mount \*\* outer edge counterweight basket